



MSMD012AB CONDENSING UNIT



Note: Pictures are for illustration only,
and may not reflect the listed model.



GENERAL						
REFRIGERANT	VOLTAGE	COMPRESSOR TYPE	COMPRESSOR MODEL	HP	AWEF	LISTINGS
R-448A/R-449A	208-230/60/1	Scroll	ZS09KAE-PFV	1.25	5.61	UL/CUL

BTUH CAPACITY (At Saturated Suction Temperature (SST) and 90° Ambient at Condenser)							
-30	-20	-10	20	25	30	35	45
-	-	-	9,919	11,028	12,261	13,628	16,811

BTUH CAPACITY (At Saturated Suction Temperature (SST) and 100° Ambient at Condenser)							
-30	-20	-10	20	25	30	35	45
-	-	-	9,126	10,146	11,280	12,537	15,466

DIMENSIONAL DATA					
OVERALL (to nearest inch)			WT (lbs)	BASE SIZE	BASE/HOOD
L	W	H			
38	27	18	240	M2	021M

INSTALLATION					
REFRIGERANT	RECEIVER TANK (lbs) 90%/90°F	CONNECTIONS			ESTIMATED TOTAL HEAT REJECTION (BTUH)
		LIQUID	SUCTION		
R-448A/R-449A	10.1	1/2	7/8		8

ELECTRICAL							
MCA	MOP	COMP VOLTS	COMP PHASE	COMP HZ	COMP RLA	COMP LRA	OTHER LOAD DATA
19	20	208-230	1	60	9	40.3	
FAN PHASE	FAN HZ	FAN FLA	FAN HP	FAN QUANTITY	MAX EVAP FAN AMPS	MAX EVAP DEF HEATER AMPS	VOLTS 208-230
1	60	0.5	1/20	2	4	15.0	PHASE 1
							AMPS 0.5

